



**Teakdecking
Systems®**

PROFESSIONAL TOOLS

“The Professional’s Choice”



TDS Seam-Sander

Designed for vertical sanding of the sides of a seam, to scuff up the edges or remove old material / residue, leaving a totally clean seam surface for the SIS440 deck caulk to bond to.

TDS Seam Sander is specially designed and constructed for long service life, and ease and speed of operation.

Made of the finest quality steel and hardwood, TDS Seam Sander is manufactured with a comfortable smooth grip and has an adjustable depth sanding surface - from 5mm to 22mm (1/5" - 7/8"). Other special sanding surfaces can be made to order.

TDS Reefing Hook

The TDS Reefing Hook is developed for clean up, removing caulk or other sealants from a seam. Before using the TDS Reefing Hook, a razor knife should be

used to free the caulk from the sides of the seam. TDS Reefing Hook is specially designed and constructed for long service life, and ease and speed of operation.

TDS Reefing Hook is made to be a fine quality tool with hand comfort in mind. Different sizes can be made to order.

Bond-Breaker Tape

Three-sided adhesion will limit the amount of movement that a seam can accept before failing. TDS recommends applying bond breaker tape at the base of every seam to create two-sided adhesion, which allows the sides of the seam to work independently from the bottom, increasing flexibility.

NOTE ! The bottom of the caulk seam should be able to move, as the deck flexes and works.



TEAKDECKING SYSTEMS. INC.
7061 15TH Street East
Sarasota, FL 34243, USA
Phone: +1 941 756 0600
Fax: +1 941 756 0406
info.usa@teakdecking.com
www.teakdecking.com



ZETA MARINE GROUP. ApS.
Gotlandsvej 6
5700 Svendborg
Denmark.
Phone: +4562201312
Fax: +4562201477
info@zetamarinegroup.com
www.zetamarinegroup.com