



**Teakdecking
Systems®**

TEAK SEALER AND PROTECTOR

TDS TEAK SEALER AND PROTECTOR is a NEW product that significantly reduces teak deck and teak trim maintenance for months!

TDS TEAK SEALER AND PROTECTOR is a water-based, polymer infused liquid that when applied to new or freshly cleaned/restored teak penetrates into the grain and forms a long lasting sub-surface barrier helping to slow oxidation (“graying”) and prevent deep-grain soiling from soot, airborne pollutants, food, beverage and lotion spills. Soiling will be kept at the surface and can be easily cleaned with a mild boat soap, or for tougher dirt, use our ECO 100/300 teak cleaners. When used on new or freshly cleaned teak, **TDS TEAK SEALER AND PROTECTOR** keeps your teak looking great for months!

PACKAGING: 0.9 liter & 3.8 liter Single component

COLOUR: Transparent

SPREADING RATE: 15 to 20 m² per liter

SHELF LIFE & STORAGE: Stored in a dry area at temperatures between 0°C - 26°C (32°-80° F) in the provided plastic cases, the Teaksealer & Promotor has a shelf life of twenty four / 24 months from the date of production. Note! Product date code on packaging is batch code and date of manufacture.

HANDLING SUGGESTIONS:

- 1.) Read and follow instructions printed on the packaging.
- 2.) Thoroughly clean teak surfaces of any dirt or oil before applying Sealer. Rinse deck thoroughly and allow to completely air dry, which can vary with conditions. Note: product will lock in moisture if applied prior to drying which may cause mold.
- 3.) Never use Cleaners that contain Acids to clean your teak surface before applying the Teaksealer.

BENEFITS:

- 1.) Easy to apply.
- 2.) Improves the non-slip properties of the teak.
- 3.) Prevents graying for months.
- 4.) Safe for the environment.
- 5.) Long lasting, up to 3 to 4 months in Mediterranean areas.
Longer during winter time. Up to 3 months in tropical climates.
- 6.) Prevents dirt and most liquids from penetrating the wood grain.
- 7.) A regular cleaning with a pH neutral boat-soap should be adequate. In case of heavier dirt/soot accumulations, use TDS ECO.100 or ECO-300 cleaner.6.) Can be used on painted surfaces and Stainless Steel.





**Teakdecking
Systems®**

TEAK SEALER AND PROTECTOR

APPLICATION:

- 1.) Temperature must be between 10 and 35 degrees C. Do not apply during midday sun.
Recommended time is before 10 am or after 2 pm.
- 2.) Apply with a brush or lint-free roller, microfiber or a mop/cotton cloth.
- 3.) Apply with the grain and add pressure to assist product into grain.
- 4.) 2 coats are required. Wait at least 2 hours before recoating. First coat must be touch dry and tack-free. Recoating should be done promptly before deck accumulates dust and dirt.
- 5.) Recommended to apply an additional coat of sealer at first sign of wear to avoid breaks in coating.
- 6.) NOTE: do not attempt to apply TDS teak Sealer to previously oiled decks without first testing a small area to be sure the oil has dissipated adequately for the sealer to penetrate. If oil is still present, sand or aggressively clean before applying.

CURING: The product is non-corrosive to all substrates. The product starts curing the moment it is exposed to air and humidity.

CAUTION: Causes eye irritation. May cause respiratory irritation. May cause damage to fertility or unborn child. Avoid breathing mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in area well ventilated. Wear protective gloves and eye protection. If in eyes, rinse with water. Remove contact lenses. Continue rinsing. If Concerned get medical attention.

WARANTY: In connection with the sales of this product, TEAKDECKING SYSTEMS Inc (TDS). makes no warranty of suitability for any specific purpose. In lieu of all warranties expressed or implied. TDS will refund the purchase price of any defective material. In no case will TDS be liable for incidental or consequential damages.



TEAKDECKING SYSTEMS. INC.
7061 15TH Street East
Sarasota, FL 34243, USA
Phone: +1 941 756 0600
Fax: +1 941 756 0406
info.usa@teakdecking.com
www.teakdecking.com



Teakdecking Systems® European representative

ZETA MARINE GROUP. ApS.
Gotlandsvej 6
5700 Svendborg
Denmark.
Phone: +4562201312
info@zetamarinegroup.com
www.zetamarinegroup.com